






Stellar Classic

	Stellar 154	Stellar 213	Stellar 290	Stellar 420	Stellar 580
Technical specifications					
Dimensions (W x H x D)	49 x 36 x 12.6 mm	70.5 x 35.2 x 12.6 mm	93.4 x 43 x 12.6 mm	104.8 x 94 x 10.5 mm	135 x 115 x 10.5 mm
Visible screen area Dimensions (W x H)	1,54 inches 27,6 x 27,6 mm	2.13 inches 48,55 x 27,6 mm	2.90 inches 66,9 x 29,06 mm	4.20 inches 84,8 x 63,6 mm	5.80 inches 118,8 x 88,36 mm
Weight	18 grams (0.51 oz)	30 grams (1.00 oz)	37 grams (1.31 oz)	60 grams (2.00 oz)	75 grams (2.40 oz)
Dots per inch (DPI)	111	111	112	120	128
Type	Black and white bistable EPD	Black and white bistable EPD	Black and white bistable EPD	Black and white bistable EPD	Black and white bistable EPD
Orientation	Landscape or Portrait	Landscape or Portrait	Landscape or Portrait	Landscape or Portrait	Landscape or Portrait
Viewing angle	Near 180° viewing angle	Near 180° viewing angle	Near 180° viewing angle	Near 180° viewing angle	Near 180° viewing angle
Appearance	Standard unit available with white bezel front,	Standard unit available with white bezel front,	Standard unit available with white bezel front,	Standard unit available with white bezel front,	Standard unit available with white bezel front,
Unit identifier barcode	Front	Front	Front	Side	Side
Operating temperature range	0°C to 40°C +32°F to 104°F	0°C to 40°C +32°F to 104°F	0°C to 40°C +32°F to 104°F	0°C to 40°C +32°F to 104°F	0°C to 40°C +32°F to 104°F
Storage temperature range	-20°C to 70°C -4°F to 158°F	-20°C to 70°C -4°F to 158°F	-20°C to 70°C -4°F to 158°F	-20°C to 70°C -4°F to 158°F	-20°C to 70°C -4°F to 158°F
Battery life	Typically 5 years (up to 5 updates/day)*	Typically 5 years (up to 5 updates/day)*	Typically 5 years (up to 5 updates/day)*	Typically 5 years (up to 5 updates/day)*	Typically 5 years (up to 5 updates/day)*
Replaceable batteries	1 x CR2450	2 x CR2450	2 x CR2450	4 x CR2450	6 x CR2450
Fittings	ESLs use our versatile system to attach easily and securely to our shelf-rails. Adapters are also available for other common fixtures and fittings.	ESLs use our versatile system to attach easily and securely to our shelf-rails. Adapters are also available for other common fixtures and fittings.	ESLs use our versatile system to attach easily and securely to our shelf-rails. Adapters are also available for other common fixtures and fittings.	ESLs use our versatile system to attach easily and securely to our shelf-rails. Adapters are also available for other common fixtures and fittings.	ESLs use our versatile system to attach easily and securely to our shelf-rails. Adapters are also available for other common fixtures and fittings.
Communications	2.4 GHz Band 2-way wireless	2.4 GHz Band 2-way wireless	2.4 GHz Band 2-way wireless	2.4 GHz Band 2-way wireless	2.4 GHz Band 2-way wireless
RF Approvals	Euro ETSI EN 302 220 USA FCC rules in Part 18 of CFR 47	European ETSI EN 302 220 USA FCC rules in Part 18 of CFR 47	European ETSI EN 302 220 USA FCC rules in Part 18 of CFR 47	European ETSI EN 302 220 USA FCC rules in Part 18 of CFR 47	European ETSI EN 302 220 USA FCC rules in Part 18 of CFR 47
Emissions	ETSI EN301- 489 FCC Part 15 Low Power Communication Device	ETSI EN301- 489 FCC Part 15 Low Power Communication Device	ETSI EN301- 489 FCC Part 15 Low Power Communication Device	ETSI EN301- 489 FCC Part 15 Low Power Communication Device	ETSI EN301- 489 FCC Part 15 Low Power Communication Device
Safety approvals	IEC 60950-1 CE, CB	IEC 60950-1 CE, CB	IEC 60950-1 CE, CB	IEC 60950-1 CE, CB	IEC 60950-1 CE, CB
Freezer version avail.		Yes	Yes	Yes	Yes
Bezel colours available	Yes (MOQ applies)	Yes (MOQ applies)	Yes (MOQ applies)	Yes (MOQ applies)	Yes (MOQ applies)

* Full replacement warranty for 5 years battery lifetime is given at an extra cost of 0,5 USD.

Technical data is subject to change at EastWest's discretion.